




# PRODUCT REFERENCE SHEET

©2020

## Universal Angle Adapter


1832 A

The Universal Snap-In Adapters are designed to be compatible with both angle and round members. The 3/4" thru holes will accommodate a variety of snap style hangers, as well as 3/8" and 10mm threaded inserts. Includes torque stop set bolt to ensure proper attachment force.




\*Patent: 10910805; 10920911

## TYPICAL APPLICATIONS



The torque stop screw has two heads. The top head will snap off when correct tightening torque is achieved. The bottom head will remain to enable adapter removal.


**1**



3-5Nm torque


Place adapter on mounting structure. Engage 1/2" wrench on top head and tighten at a slow and steady pace. The top head is designed to snap at the correct torque. Do not tighten further.

**2**




Adapter is shown here with the top head completely snapped off. This is the properly installed condition.

**3**



For removal, use bottom head to unscrew with 1/2" wrench head.



Maximum loading: 3 polymer hangers (shown) or two metal hangers.

Hanger	Stack Height
SSH-47	PIM free hanger for 4 to 7 mm cables
SSH-710	PIM free hanger for 7.1 to 10 mm cables
SSH-1014	PIM free hanger for 10.1 to 14 mm cables
SSH-1416	PIM free hanger for 14.1 to 16 mm cables