INSTALLATION INSTRUCTIONS

Feed-thru Entry Panels
for Coaxial Cable Applications

PRODUCT DESCRIPTION

Aluminum Feed-thru Entry Panels enable multiple coax runs to enter buildings and shelters. Rugged EP-Series entry panels support coax at the entry point and prevent moisture from entering the building. EP panels feature a 4" (101.6mm) or 5" (127mm) opening to accept boot assemblies. They can be used in both interior and exterior wall mounting applications. Each feed-thru entry panel includes a set of wall attachment hardware including #14 stainless steel screws, finishing washers and plastic anchors. A powder-coated finish supplies entry port panels with an aesthetically pleasing appearance and protection against extreme environmental conditions. Sealing caps for all openings are included.

NOTICE

Installation of this product should only be performed by trained, qualified and experienced personnel. Installation instructions for this product should be read thoroughly before installation is performed. The manufacturer and supplier of this product disclaims any liability or responsibility for the results of improper or unsafe installation practice.

MATERIAL LIST

- EP-Series Entry Panel
- Hardware Kit
  Hardware Kit contains:
  a) PL-138#14 (Plastic Anchors)
  b) SW-F#14 (SS Finishing Washers)
  c) SO-14x150 (SS Oval Tapping Screws)

(Hardware kit material quantities vary according to entry panel ordered.)

REQUIRED TOOLS

- Drill
- Phillips Head Screwdriver bit
- 5/16" Drill Bit
- Hammer
- Tape Measure
- Caulking Gun with Tube of Silicon

TYPICAL APPLICATIONS

NOTE: For a better anchor bond, fill pre-drilled holes with silicon before inserting anchor

Existing Wall

Pre-drilled 5/16" Hole

PL-138#14
PLASTIC ANCHORS
(Included)

Wall Opening

EP-1449
ENTRY PANEL
(Shown)

SO-14x150
SS OVAL TAPPING
SCREW
(Included)

SW-F#14
SS FINISHING WASHERS
(Included)